



Ultra-Containment Berm Mini Foamwall Model®

SPECIFICATIONS

KEY FEATURES AND BENEFITS

- + Compact and easy to store, but deploy in seconds for rapid spill response.
- + Foldable and secured using the attached strap for simple and convenient transport and storage.
- + Foam sidewalls (6"H) provide support but can be driven over or stepped on for easier equipment or vehicle placement.
- + Heavy-duty 22 oz. PVC construction provides excellent durability and chemical compatibility.
- + Versatile: applications range from equipment and container storage to loading/unloading and field maintenance operations



Part#	Dimensions in. (mm) Wall Height: 6 in. (152 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8845	36 x 36 (914.4 x 914.4)	33 (125)	5 (2.27)
8846	60 x 60 (1524 x 1524)	93.5 (354)	9 (4.1)
8847	72 x 72 (1829 x 1829)	134.5 (509.14)	12 (5.44)
8850	24 x 24 (609.6 x 609.6)	15 (56.8)	3.00 (1.4)
8852	48 x 48 (1219.2 x 1219.2)	60 (227.1)	7.00 (3.2)
8854	48 x 72 (1219.2 x 1828.8)	75 (283.9)	9.00 (4.1)

PVC MATERIAL SPECS

	English	Metric	Testing Method
Weight	22 oz./yd ²	745 g/m ²	FS 5040 / ASTM D3776
Width	up to 126"	up to 320 cm	-
Count	18 x 16/1"	7 x 7/cm	-
Denier	1300 x 1500	1430 x 1650	-
Grab Tensile	459 x 418 lbs./1"	2042 x 1859 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	140 x 150 lbs./1"	623 x 667 N/2.5 cm	FS 5134 / ASTM 2261
Adhesion	22 lbs./2"	98 N/5 cm	FS 5970 / ASTM D751
Finish	Matte		
Cold Crack	-30°F	-34°C	FS 5874 / ASTM D2136
Treatments	Anti-Mildew, UV Pigments		
Put-Up	75 yds	69 m	